

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-341
Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year Ford Motor Company emission control systems are certified as described below for gasoline-powered passenger cars:

<u>Engine Family</u>	<u>Displacement</u>		<u>Exhaust Emission Control Systems</u> <u>(Special Features)</u>
	<u>Liters</u>	<u>(Cubic Inches)</u>	
JFM2.3V5FFG0	2.3	(140)	Exhaust Gas Recirculation Heated Oxygen Sensor Three-Way Catalyst (Two) (Electronic Port Fuel Injection) (On-Board Diagnostics)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

<u>Hydrocarbons</u> <u>Grams per Mile</u>	<u>Carbon Monoxide</u> <u>Grams per Mile</u>	<u>Nitrogen Oxides</u> <u>Grams per mile</u>
0.39	7.0	0.7

The following are the certification emission values for this engine family:

<u>Hydrocarbons</u> <u>Grams per Mile</u>	<u>Carbon Monoxide</u> <u>Grams per Mile</u>	<u>Nitrogen Oxides</u> <u>Grams per Mile</u>
0.14	2.6	0.2

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.


BE IT FURTHER RESOLVED: That the vehicle models listed also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s] ..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.) and with Health and Safety Code Section 43204.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 19th day of June, 1987.


K. D. Drachand, Chief
Mobile Source Division

Manufacturer Ford Motor Company Engine Family JFM2.3V5FFGO
 Evaporative Family 8HMJ Engine Type Otto Spark I4
 Liters (CID) 2.3 (140)

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance
 ECU-Electronic Control Unit
 EI-Electronic Ignition
 ESAC-Electronic Spark Advance Control
 VA-Vacuum Advance
 VR-Vacuum Retard

Exhaust Emissions Control System

AIP-Air Injection-Pump
 AIV-Air Injection-Valve
 DBC-Dual Bed Catalyst
 EGR-Exhaust Gas Recirculation
 EIC-Electronic Injection Control
 EM-Engine Modification
 OC-Oxidation Catalyst
 OS-Oxygen Sensor
 HOS-Heated Oxygen Sensor
 SPL-Smoke Puff Limiter or Throttle Delay
 TOC-Trap Oxidizer, Continual
 TOP-Trap Oxidizer, Periodical
 TWC-Three-Way Catalyst
 WUOC-Warm-Up Oxidation Catalyst
 WUTWC-Warm-Up Three-Way Catalyst

Special Features

CCV-Combustion Chamber Valve
 CFI-Central Fuel Injection or Throttle Body Injection
 DID-Diesel Injection-Direct
 DIP-Diesel Injection-Prechamber
 EFI-Electronic Fuel Injection
 IC-Intercooler or Aftercooler
 MFI-Mechanical Fuel Injection
 OBD-On-Board Diagnostics
 TC-Turbocharger

Fuel System

CFI, CL, DID, DIP, EFI, MFI
 nV-nVenturi Carburetor

VEHICLE MODELS:

Mustang (2-DR, 3-DR, Convertible)

Engine: Front X Mid. Rear
 Drive: FWD RWD X 4WD Full Time 4WD Part Time

19⁸⁸ AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEETE.O. # A-10-341Passenger Cars X Light-Duty Trucks _____ Medium-Duty Vehicles _____ Gas X Diesel _____ Page 2Manufacturer Ford Motor Company Engine Family JFM2.3V5FFGOLiter (CID) 2.3 (140) Eng. Type Otto Spark I-4Emission Control Sys. (Special Features) ECU, ESAC, EGR, HOS, (EFI) TWC-2

Engine Code	Vehicle Models (If Coded see attachment) (Dyno Hp) ⁽¹⁾	Trans. Type	Equiv. Test Weight	Ign. System (ECU) 12A650 Part No.	Fuel System 9F593 Part No.	EGR Valve 9F493 Part No.	Catalyst 5E212 Part No.
705AR11A (w/Air Con.)	Mustang 2-DR	M5X397 (Manual)	3125	E7TF-BC	E59E-AB	E7ZE-BB	E7ZC-AA
	Mustang 3-DR	"	3250				E7ZC-AD (Alt)
	Mustang-Conv.	"	3375				
705AR11N (Non-Air)	Mustang 2-DR	M5X397 (Manual)	3125				
	Mustang 3-DR	"	3250				
	Mustang-Conv.	"	3375				
706AR10A (w/Air Con.)	Mustang 2-DR	A4X023 (Auto)	3125				
	Mustang 3-DR	"	3250				
	Mustang-Conv.	"	3375				
706AR10N (Non-Air)	Mustang 2-DR	A4X023 (Auto)	3125				
	Mustang 3-DR	"	3250				
	Mustang-Conv.	"	3375				
(1) Non-Air 8.7 w/Air 9.6							

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

Date of Issue _____ Revisions: _____

E.O. # A-10-341

1988 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Page 3Passenger Cars X light-Duty Trucks _____ Medium-Duty Vehicles _____ Gas X Diesel _____Manufacturer Ford Motor Company Engine Family JFM2.3V5FFG0Liter (CID) 2.3 (140) Eng. Tyoe OTTO SPARKEmission Control Sys. (Special Features) ECU, ESAC, EGR OS, EFI

Engine Code	Vehicle Models (If Coded see attachment) (Dyno Hp)	Trans. Type	Equiv. Test Weight	Ign. System (ECU) Part No. 12A650	Fuel System Part No. 9F593	EGR Valve Part No. 9F493	Catalyst Part No. 5E212
805AR10A	Mustang 2-Dr (9.7)	Manual	3125	E8TF-CUA	E59E-AB	E7ZE-BB	E7ZE-AA
	Mustang 3-Dr (9.4)		3250				E7ZC-AD (Alt.)
	Mustang Conv. (9.6)		3375				
805AR10N	Mustang 2-Dr (8.8)		3125				
	Mustang 3-Dr (8.5)		3125				
	Mustang Conv. (8.7)		3250				
806AR10A	Mustang 2-Dr (9.7)	Auto	3125				
	Mustang 3-Dr (9.4)		3250				
	Mustang Conv. (9.6)		3375				
806AR10N	Mustang 2-Dr (8.8)		3125				
	Mustang 3-Dr (8.5)		3250				
	Mustang Conv. (8.7)		3375				

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufactureres HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

Date of Issue 2-9-88 Revisions: 3-25-88